

## FX 12 GH

SINGLE-PHASE POWER GENERATOR / OUTPUT POWER **11 KVA**  
SINGLE-PHASE / PETROL ENGINE **3000 RPM**

<b>Gen Set Features</b>	+ Low oil level cut out device + 12 V built-in battery with electric start + 1 x 32 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB) + Voltmeter + Hourmeter + Central lifting eye	
<b>Gen Set Options</b> (available as factory options)	+ Version with different voltages + 60 Hz version + AMF/ATS panel for auto start operation	
<b>Accessories on Request</b>	+ Trolley	two-wheels and handles
<b>Noise Level</b>	+ Lwa 98	(73 dB a 7 m)
<b>AC Generator 50 Hz</b>	+ Type	synchronous
	+ Single-phase p. (stand-by)	11 kVA - 230 V
	+ Single-phase p. (prime)	10 kVA - 230 V
	+ Power Factor	0,8
<b>Petrol Engine 3000 rpm</b>	+ Type	<b>Honda GX 630 OHV</b> - 2 cil. 14,1 CV (10,5 kWm) - 688 cm <sup>3</sup>
	+ Fuel	Petrol
	+ Cooling system	air
	+ Starting system	electric
	+ Fuel tank capacity	29 l
	+ Fuel consumption @ 75%	6 l/h (@ 3600 rpm)
<b>Other features</b>	+ Insulation Class	H
	+ Ambient temperature	40 °C
	+ Altitude	1000 mt
	+ Mechanical Protection	IP 23
	+ Dimensions (L x W x H)	940 x 488 x 823 mm
	+ Dry weight	148 kg

## FX 12 GH



**mase**  
GENERATORS