




Product Service

# CERTIFICATE

No. Z2 076043 0091 Rev. 05

**Holder of Certificate:** Hengdian Group DMEGC Magnetics CO., LTD  
Hengdian Industrial Zone  
322118 Dongyang, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:** Crystalline Silicon Terrestrial Photovoltaic (PV) Modules  
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704061905408-05

**Valid until:** 2027-01-16

**Date,** 2022-01-17

( David Bo )

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICATE

# CERTIFICATE

No. Z2 076043 0091 Rev. 05

## Model(s):

DMxxx-M156-72-V, (xxx=335-375, in steps of 5)  
DMxxx-M156-60-V, (xxx=280-310, in steps of 5)  
DMHxxxM6-144SW-V, (xxx=340-385, in steps of 5)  
DMHxxxM6-120SW-V, (xxx=280-320, in steps of 5)  
DMxxx-M156-72P-V, (xxx=335-375, in steps of 5)  
DMxxx-M156-60P-V, (xxx=280-310, in steps of 5)  
DMxxx-M156-36P-V, (xxx=175-190, in steps of 5)  
DMxxx-M159-72-V, (xxx=385-395, in steps of 5)  
DMxxx-M159-60-V, (xxx=315-330, in steps of 5)  
DMHxxxM6A-144SW-V, (xxx=380-405, in steps of 5)  
DMHxxxM6A-120SW-V, (xxx=320-350, in steps of 5)  
DMxxxM6-72HSW-V, (xxx=415-450, in steps of 5)  
DMxxxM6-60HSW-V, (xxx=345-375, in steps of 5)  
DMxxxM6-72HBW-V, (xxx=415-450, in steps of 5)  
DMxxxM6-60HBW-V, (xxx=345-375, in steps of 5)  
DMHxxxM6A-144BW-V, (xxx=380-405, in steps of 5)  
DMHxxxM6A-120BW-V, (xxx=320-350, in steps of 5)  
DMxxxG1-60SW-V, (xxx=315-330, in steps of 5)  
DMxxxG1-60BW-V, (xxx=315-330, in steps of 5)  
DMxxxG1-60HSW-V, (xxx=320-350, in steps of 5)  
DMxxxG1-60HBW-V, (xxx=320-350, in steps of 5)  
DMxxxG1-72SW-V, (xxx=385-395, in steps of 5)  
DMxxxG1-72BW-V, (xxx=385-395, in steps of 5)  
DMxxxG1-72HSW-V, (xxx=380-405, in steps of 5)  
DMxxxG1-72HBW-V, (xxx=380-405, in steps of 5)  
DMxxxM2-60SW-V, (xxx=280-310, in steps of 5)  
DMxxxM2-60BW-V, (xxx=280-310, in steps of 5)  
DMxxxM2-60HSW-V, (xxx=280-320, in steps of 5)  
DMxxxM2-60HBW-V, (xxx=280-320, in steps of 5)  
DMxxxM2-72SW-V, (xxx=335-375, in steps of 5)  
DMxxxM2-72BW-V, (xxx=335-375, in steps of 5)  
DMxxxM2-72HSW-V, (xxx=340-385, in steps of 5)  
DMxxxM2-72HBW-V, (xxx=340-385, in steps of 5)  
DMxxxM10-72HSW-V, (xxx=535-555, in steps of 5)  
DMxxxM10-72HBW-V, (xxx=535-555, in steps of 5)  
DMxxxM10-60HSW-V, (xxx=435-460, in steps of 5)  
DMxxxM10-60HBW-V, (xxx=435-460, in steps of 5)  
DMxxxG12-66HSW-V, (xxx=650-660, in steps of 5)  
DMxxxG12-66HBW-V, (xxx=650-660, in steps of 5)  
DMxxxG12-60HSW-V, (xxx=590-600, in steps of 5)  
DMxxxG12-60HBW-V, (xxx=590-600, in steps of 5)  
DMxxxM10-54HSW-V, (xxx=380-415, in steps of 5)  
DMxxxM10-54HBW-V, (xxx=380-415, in steps of 5)  
DMxxxM6S-72HSW-V, (xxx=415-455, in steps of 5)  
DMxxxM6S-72HBW-V, (xxx=415-455, in steps of 5)  
DMxxxM6S-72HBB-V, (xxx=415-455, in steps of 5)  
DMxxxM6S-60HSW-V, (xxx=345-380, in steps of 5)  
DMxxxM6S-60HBW-V, (xxx=345-380, in steps of 5)  
DMxxxM6S-60HBB-V, (xxx=345-380, in steps of 5)  
DMxxxM6-54HSW-V, (xxx=315-340, in steps of 5)  
DMxxxM6-54HBW-V, (xxx=315-340, in steps of 5)  
DMxxxM6-54HBB-V, (xxx=315-340, in steps of 5)  
DMxxxM10-66HSW-V, (xxx=480-505, in steps of 5)  
DMxxxM10-66HBW-V, (xxx=480-505, in steps of 5)  
DMxxxM10-66HBB-V, (xxx=480-505, in steps of 5)  
DMxxxM10-66HSW-V, (xxx=480-505, in steps of 5)  
DMxxxM10-66HBW-V, (xxx=480-505, in steps of 5)  
xxx is standing for the rated output power at STC



# CERTIFICATE

No. Z2 076043 0091 Rev. 05

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed, with Junction box, cable and connector.
Fire Safety Class:	Class C according to UL790.

## Tested according to:

IEC 61215-1:2016  
IEC 61215-1-1:2016  
IEC 61215-2:2016  
IEC 61730-1:2016  
IEC 61730-2:2016  
IEC 62716:2013